

Technical Specifications

Split Air Conditioner Indoor Unit

| Sr No | Parameter | Unit | Value |
|-------|---|-------------------|--------------------------|
| 1 | Model | — | GKH18BA-K3DNA2A/I |
| 3 | Type | — | Cassette |
| 4 | Cooling Capacity | kW | 4.50 |
| 6 | Heating Capacity | kW | 5.00 |
| 8 | Air Flow Volume(SS/H/MH/M/ML/L/SL) | m ³ /h | /600/ /500/ /450/ |
| 14 | Sound Pressure Level (SS/H/MH/M/ML/L/SL) | dB (A) | /46/ /44/ /42/ |
| 16 | Dehumidifying Volume | L/h | 1.8 |
| 18 | Rated Voltage | V | 220-240 |
| 19 | Rated Frequency | Hz | 50 |
| 20 | Phases | — | 1 |
| 21 | Cross-sectional Area of Power Cable Conductor | mm ² | 1.00 |
| 22 | Recommended Power Cable(Core) | N | 4 |
| 23 | Fuse Current | A | 3.15 |
| 53 | Gas Pipe(to indoor unit) | mm | 1/2" |
| 54 | Liquid pipe | mm | 1/4" |
| 55 | Connection method | — | Flare Connection |
| 56 | Drain Connection (outer diameter) | mm | Φ31 |
| 57 | Dimension of Outline(W×D×H) | mm | 570×570×230 |
| 60 | Net Weight | kg | 18.0 |