

1W Cassette	Heat pump		GMV-ND22TD/A-T	GMV-ND28TD/A-T	GMV-ND36TD/A-T	GMV-ND45TD/A-T	GMV-ND50TD/A-T
Capacity	Cooling	kW	2.20	2.80	3.60	4.50	5.00
	Heating	kW	2.50	3.20	4.00	5.00	5.60
Power supply		V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
Motor power input	W		30	30	30	30	30
Power consumption	kW		30	30	30	30	30
Air flow volume	m ³ /h		600	600	600	830	830
Standard Esp	Pa		0	0	0	0	0
Sound pressure level	dB(A)		36/28	36/28	36/28	40/32	40/32
Connecting pipe	Gas	inch	3/8	3/8	1/2	1/2	1/2
	Liquid	inch	1/4	1/4	1/4	1/4	1/4
Drain pipe	External dia.	mm	Φ25	Φ25	Φ25	Φ25	Φ25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Outline dimension Body	W	mm	987	987	987	987	987
	D	mm	385	385	385	385	385
	H	mm	178	178	178	178	178
Outline dimension Panel	W	mm	1200	1200	1200	1200	1200
	D	mm	460	460	460	460	460
	H	mm	55	55	55	55	55
Net Weight	Body	kg	20.0	20.0	20.0	21.0	21.0
	Panel	kg	4.2	4.2	4.2	4.2	4.2