

Fresh Air Ducted	Heat pump		GMV-NX140P/A<X1.2>-K	GMV-NX224P/A<X2.0>-M	GMV-NX280P/A<X2.5>-M	GMV-NX280P/A<X3.0>-M	GMV-NX450P/A<X4.0>-M
Capacity	Cooling	kW	14.00	22.40	28.00	28.00	45.00
	Heating	kW	10.00	16.00	20.00	20.00	32.00
Power supply	V/Ph/Hz		220-240/1/50	380-415/3/50	380-415/3/50	380-415/3/50	380-415/3/50
Motor power input	W		/	/	/	/	/
Power consumption	kW		/	/	/	/	/
Air flow volume	m ³ /h		1200	2000	2500	3000	4000
	CFM		706	1177	1471	1766	2354
Standard Esp	Pa		150	200	200	200	200.0
Sound pressure level	dB(A)		42	47	48	51	58
Connecting pipe	Gas	inch	5/8	3/4	7/8	7/8	1 1/8
	Liquid	inch	3/8	3/8	3/8	3/8	1/2
	Connection method		Flare Connection	Brazing Connection	Brazing Connection	Brazing Connection	Brazing Connection
Drain pipe	External dia.	mm	25	25	25	25	25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5
Outline dimension Body	W	mm	1463	1500	1500	1500	1700
	D	mm	756	1000	1000	1000	1100
	H	mm	300	500	500	500	650
Net Weight	Body	kg	63.5	130.0	134.0	134.0	208.0