

Model			GMV-120WL/A-T	GMV-140WL/A-T	GMV-160WL/A-T
Capacity	Cooling	kW	12.10	14.00	16.00
	Heating	kW	14.00	16.50	18.50
Connection Ratio		%	15~135	15~135	15~135
EER		kW/kW	3.97	3.52	3.30
COP		kW/kW	4.28	4.14	3.96
Power supply		V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50
Rated input	Cooling	kW	3.05	3.98	4.85
	Heating	kW	3.27	3.99	4.67
Rated current	Cooling	A	15	19.2	23.4
	Heating	A	15.8	19.3	23
Refrigerant	Type		R410A	R410A	R410A
	Charge volume	kg	5.0	5.0	5.0
Airflow rate		m³/h	6000	6300	6600
Wiring connection	Cable size	mm²	4.00	4.00	6.00
Piping	Gas Pipe size	inch	5/8	5/8	3/4
	Liquid Pipe size	inch	3/8	3/8	3/8
Sound pressure level		dB(A)	55	56	58
Outline dimension	W	mm	900	900	900
	D	mm	340	340	340
	H	mm	1345	1345	1345
Net weight		kg	110.0	110.0	110.0
Maximum IDU NO.		unit	7	8	9
Max. equivalent pipe length		m	120	120	120
Recommended Circuit breaker		A	32	32	40