

Ducted (Lo ESP)	Heat pump		GMV-ND22PL/B-T	GMV-ND25PL/B-T	GMV-ND28PL/B-T	GMV-ND32PL/B-T	GMV-ND36PL/B-T	GMV-ND40PL/B-T	GMV-ND45PL/B-T	GMV-ND50PL/B-T	GMV-ND56PL/B-T	GMV-ND63PL/B-T	GMV-ND72PL/B-T
	Capacity	Cooling	kW	2.20	2.50	2.80	3.20	3.60	4.00	4.50	5.00	5.60	6.30
Heating		kW	2.50	2.80	3.20	3.60	4.00	4.50	5.00	5.60	6.30	7.00	8.00
Power supply	V/Ph/Hz		220-240/1/50	220-240 / 208-230/1/50 / 60	220-240/1/50	220-240 / 208-230/1/50 / 60	220-240 / 208-230/1/50 / 60	220-240 /1/50	220-240 /1/50	220-240 /1/50	220-240 /1/50	220-240 /1/50	220-240 /1/50
Motor power input	W		60	60	60	60	60	60	60	60	60	60	60
Air flow volume	m ³ /h		450	450	450	550	550	750	750	750	850	850	1100
	CFM		264.825	264.825	264.825	323.675	323.675	441.375	441.375	441.375	500.225	500.225	647.35
Standard Esp	Pa		0/15	0/15	0/15	0/15	0/15	0/15	0/15	0/15	0/15	0/15	0/15
Sound pressure level	dB(A)		30/22	30/22	30/22	31/25	31/25	33/27	33/27	33/27	35/29	35/29	37/30
Connecting pipe	Gas	inch	3/8"	3/8"	3/8"	3/8"	1/2"	1/2"	1/2"	1/2"	5/8"	5/8"	5/8"
	Liquid	inch	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	1/4"	3/8"	3/8"	3/8"
Drain pipe	External dia.	mm	25	25	25	25	25	25	25	25	25	25	25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5	2.5
Outline dimension Body	W	mm	710	710	710	710	710	1010	1010	1010	1010	1010	1310
	D	mm	450	450	450	450	450	450	450	450	450	450	450
	H	mm	200	200	200	200	200	200	200	200	200	200	200
Net Weight	Body	kg	18.5	18.5	18.5	19.5	19.5	23.5	23.5	23.5	24.5	24.5	30.5