

Model			GMV-120WL/A-X	GMV-140WL/A-X	GMV-160WL/A-X
Capacity	Cooling	kW	12.10	14.00	16.00
	Heating	kW	14.00	16.50	18.50
Connection ratio		%	15~135	15~135	15~135
EER		kW/kW	3.97	3.52	3.30
COP		kW/kW	4.28	4.14	3.96
Power supply		V/Ph/Hz	380-415/3/50	380-415/3/50	380-415/3/50
Rated input	Cooling	kW	3.05	3.98	4.85
	Heating	kW	3.27	3.99	4.67
Rated current	Cooling	A	5.2	6.4	7.6
	Heating	A	5.8	6.8	7.8
Refrigerant	Type		R410A	R410A	R410A
	Charge volume	kg	5.0	5.0	5.0
Airflow rate		m ³ /h	6000	6300	6600
Wiring connection	Cable size	mm ²	2.5	2.5	2.5
	Gas Pipe size	inch	5/8	5/8	3/4
	Liquid Pipe size	inch	3/8	3/8	3/8
Sound pressure level		dB(A)	55	56	58
Outline dimension	W	mm	900	900	900
	D	mm	340	340	340
	H	mm	1345	1345	1345
Net weight		kg	120.0	120.0	130.0
Maximum IDU NO.		unit	7	8	9
Max. equivalent pipe length		m	120	120	120
Recommended Circuit breaker		A	16	16	16