

| Model | | | GMV-224WL/A-X | GMV-250WL/A-X | GMV-280WL/A-X |
|-----------------------------|------------------|-------------------|---------------|---------------|---------------|
| Capacity | Cooling | kW | 22.40 | 25.00 | 28.00 |
| | Heating | kW | 25.00 | 28.00 | 30.00 |
| Connection Ratio | | % | 10~100 | 10~100 | 10~100 |
| EER | | kW/kW | 3.34 | 3.38 | 3.37 |
| COP | | kW/kW | 3.82 | 3.81 | 3.68 |
| Power supply | | V/Ph/Hz | 380-415/3/50 | 380-415/3/50 | 380-415/3/50 |
| Rated input | Cooling | kW | 6.70 | 7.40 | 8.30 |
| | Heating | kW | 6.54 | 7.35 | 8.15 |
| Rated current | Cooling | A | 13.0 | 13.5 | 14.6 |
| | Heating | A | 12.7 | 12.9 | 14.1 |
| Refrigerant | Type | | R410A | R410A | R410A |
| | Charge volume | kg | 7.2 | 7.6 | 7.6 |
| Airflow rate | | m ³ /h | 9000 | 9000 | 9000 |
| Wiring connection | Cable size | mm ² | 4 | 4.00 | 4.00 |
| | Gas Pipe size | inch | 7/8 | 7/8 | 7/8 |
| | Liquid Pipe size | inch | 3/8 | 3/8 | 3/8 |
| Sound pressure level | | dB(A) | 60 | 61 | 61 |
| Outline dimension | W | mm | 1098 | 1098 | 1098 |
| | D | mm | 399 | 399 | 399 |
| | H | mm | 1584 | 1584 | 1584 |
| Net weight | | kg | 175.0 | 185.0 | 185.0 |
| Maximum drive IDU NO. | | unit | 13 | 16 | 16 |
| Max. equivalent pipe length | | m | 120 | 120 | 120 |
| Recommended Circuit breaker | | A | 25 | 25 | 25 |