

4W Compact Cassette	Heat pump		GMV-ND22T/B-T	GMV-ND28T/B-T	GMV-ND36T/B-T	GMV-ND45T/B-T	GMV-ND50T/B-T	GMV-ND56T/B-T
Capacity	Cooling	kW	2.20	2.80	3.60	4.50	5.00	5.60
	Heating	kW	2.50	3.20	4.00	5.00	5.60	6.30
Power supply		V/Ph/Hz	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50	220-240/1/50
Power consumption		kW	0.035	0.035	0.035	0.045	0.045	0.045
Air flow volume		m ³ /h	600	600	600	700	700	700
Standard Esp		Pa	0	0	0	0	0	0
Sound pressure level		dB(A)	41	41	41	45	45	45
Connecting pipe	Gas	inch	3/8	3/8	1/2	1/2	1/2	2/3
	Liquid	inch	1/4	1/4	1/4	1/4	1/4	3/8
Drain pipe	External dia.	mm	Φ25	Φ25	Φ25	Φ25	Φ25	Φ25
	Thickness	mm	2.5	2.5	2.5	2.5	2.5	2.5
Outline dimension Body	W	mm	596	596	596	596	596	596
	D	mm	596	596	596	596	596	596
	H	mm	240	240	240	240	240	240
Outline dimension Panel	W	mm	670	670	670	670	670	670
	D	mm	670	670	670	670	670	670
	H	mm	50	50	50	50	50	50
Net Weight	Body	kg	20.5	20.5	20.5	20.5	20.5	20.5
	Panel	kg	3.5	3.5	3.5	3.5	3.5	3.5