

| Wall Mounted              | Heat pump         |         | GMV-N22G/A3A-K | GMV-N28G/A3A-K | GMV-N36G/A3A-K | GMV-N45G/A3A-K | GMV-N50G/A3A-K | GMV-N56G/A3A-K | GMV-N63G/A3A-K | GMV-N71G/A3A-K |
|---------------------------|-------------------|---------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|----------------|
|                           | Cooling           | Heating |                |                |                |                |                |                |                |                |
| Capacity                  | Cooling           | kW      | 2.20           | 2.80           | 3.60           | 4.50           | 5.00           | 5.60           | 6.30           | 7.10           |
|                           | Heating           | kW      | 2.50           | 3.20           | 4.00           | 5.00           | 5.80           | 6.30           | 7.00           | 7.50           |
| Power supply              | V/Ph/Hz           |         | 220-240/1/50   | 220-240/1/50   | 220-240/1/50   | 220-240/1/50   | 220-240/1/50   | 220-240/1/50   | 220-240/1/50   | 220-240/1/50   |
| Motor power input         | W                 |         | 50             | 50             | 60             | 60             | 60             | 70             | 70             | 70             |
| Power consumption         | kW                |         | /              | /              | /              | /              | /              | /              | /              | /              |
| Air flow volume           | m <sup>3</sup> /h |         | 500            | 500            | 630            | 630            | 630            | 750            | 750            | 750            |
| Standard Esp              | Pa                |         | 0              | 0              | 0              | 0              | 0              | 0              | 0              | 0              |
| Sound pressure level      | dB(A)             |         | 38/34          | 38/34          | 44/38          | 44/38          | 44/38          | 44/38          | 44/38          | 44/38          |
| Connecting pipe           | Gas               | inch    | 3/8            | 3/8            | 1/2            | 1/2            | 1/2            | 5/8            | 5/8            | 5/8            |
|                           | Liquid            | inch    | 1/4            | 1/4            | 1/4            | 1/4            | 1/4            | 3/8            | 3/8            | 3/8            |
| Drain pipe                | External dia.     | mm      | Φ20            | Φ20            | Φ20            | Φ20            | Φ20            | Φ30            | Φ30            | Φ30            |
|                           | Thickness         | mm      | 1.5            | 1.5            | 1.5            | 1.5            | 1.5            | 1.5            | 1.5            | 1.5            |
| Outline dimension<br>Body | W                 | mm      | 843            | 843            | 940            | 940            | 940            | 1008           | 1008           | 1008           |
|                           | D                 | mm      | 180            | 180            | 200            | 200            | 200            | 221            | 221            | 221            |
|                           | H                 | mm      | 275            | 275            | 298            | 298            | 298            | 319            | 319            | 319            |
| Net Weight                | Body              | kg      | 10.0           | 10.0           | 12.5           | 12.5           | 12.5           | 15.0           | 15.0           | 15.0           |